

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 September 2005 (29.09.2005)

PCT

(10) International Publication Number
WO 2005/090914 A1

(51) International Patent Classification⁷: **G01C 19/56**

(21) International Application Number:
PCT/US2005/008361

(22) International Filing Date: 11 March 2005 (11.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/552,652 12 March 2004 (12.03.2004) US

(71) Applicant (for all designated States except US): **GYRATION, INC.** [US/US]; Building C, 12950 Saratoga Avenue, Saratoga, California 95070 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HOTELLING, Steven, Porter** [US/US]; 1351 Hidden Mine Road, San Jose, California 95120 (US). **BAYER, Lex** [ZA/US]; 691

Roble Avenue, #4, Menlo Park, California 94306 (US). **LAND, Brian, R.** [US/US]; 2726 Sussex Way, Redwood City, California 94061 (US).


(74) Agents: **TRIPOLI, Joseph, S.** et al.; Two Independence Way, Suite #200, Princeton, New Jersey 08540 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: DIGITAL ELECTRONICS ON SUSPENDED ASSEMBLY



(57) Abstract: A vibratory rotational rate gyroscope has a suspended assembly isolated from external vibrations by an arrangement of helical springs. This isolated assembly includes both the active components of the rotational rate gyroscope and a digital processing circuit. The digital processing circuit includes digital storage for both externally determined and internally determined unit-specific calibration values. These values provide seed values for startup processes, which improves loop startup time, and values for unit-specific electronic calibration. The digital processing circuit further converts all data to digital form. A digital communications protocol is used to transmit the calibration information and the outgoing data to and from the isolated assembly on only two conductors. Two additional conductors used for power. Four of the helical springs used in the suspension arrangement are used for these conductors such that no additional wiring is required.

WO 2005/090914 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*